



DRIVE Marine Services

Glue Guide	Purbond Polyurethane Glue	Bote Cote Epoxy Resin	Epoxy-E-Glue	QuickCure 5 Epoxy A SYSTEM THREE Product
		High adhesive strength! The leading single pack waterproof polyurethane adhesive Australia's Answer to GORRILLA Glue	ultimate strength waterproof coating. Not brittle when cured, low odour, safest to use,!	"Australia's economical & easy to use high strength solution for waterproof joints" Not brittle when cured, low odour, safest to use, ultimate strength!
Best For	- Excellent for tight fitting joints - Minimal strength where there is gap - Refer to tips sheet	- High strength adhesive & protective coating - laminating resin and for rot prevention	- Great strength with gap - Excellent adhesion to most materials - Great when clamping hard	- Tough repairs requiring durable bond, gap filling, and solvent resistance - Where fast grab required
Open Working Time	10-15 minutes	20-80 minutes depending on hardener and temperature	40 minutes	5 minutes
Clamp Time	1-2 hours - Clamp tightly!	Lightly clamp or secure in place overnight	Lightly clamp or secure in place overnight	As needed to form initial bond
Drying time	60% in 1-2 hours	Temperature dependent – at least overnight	Temperature dependent – Full Cure within 24 hours at temperatures above 15°C	5 minutes (at room temperature)
Outdoor use	100% Waterproof Excellent solvent resistance	100% Waterproof	100% Waterproof	Water Resistant - Not recommended for extended immersion in water
Glue Expansion	Yes	None	None	None
Dry Colour	Light Brown – no glue line	Clear or Translucent or can be pigmented	Translucent or timber colour or colour can be pigmented	Clear!
Finish	Sandable, stainable, paintable	Sandable, Paintable	Sandable, Paintable	Sandable
USES:				
Wood, Cardboard	✓	✓	✓	✓
Metal	✓	✓	✓	✓
Fibreglass	X	✓	✓	✓
Glass	X	✓	✓	✓
Ceramics	✓	✓	✓	✓
Foam	✓	✓	✓	✓
Plastic, PVC Sheet*	✓	✓	✓	✓
Rubber	✓	✓	✓	✓
Brick, Concrete, Stone	✓	✓	✓	✓

*Bonds most plastics, polyethylene or polypropylene need special technique

For a Comprehensive Range of Boat Building requirements including

Bote Cote Epoxies, Fillers, Pour-on-Gloss Decoupage Coating, COP-R-BOTE Epoxy Antifouling, AQUACOTE Polyurethane Coatings, PURBOND Waterproof Single Pack Glue, TREDGRIP Rubberised non-slip Paint, Glass & Carbon Reinforcing Fabrics, FERONITE Rust converter and Primer, Marine, Proof & Aircraft Plywoods, NIDAPLAST Composites, S/S & Bronze Fasteners DAVEY Traditional Bronze & Marine Fittings

BEVERLY HILLS NSW 2209

Ph. (O)02 9533 5470 (F)02 9594 4250

Email- Bote.Cote@optusnet.com.au

www.BoatCraftNSW.com.au

This site is © Drive Marine Services, All Rights Reserved